



UNI V2

-50°C to +150°C



Product Details:

- 1-ply neoprene coated glass fibre fabric
- visible bronze plated steel wire helix
- V2P 1ply neoprene coated polyamide for applications with flexing polyamide is far more durable
- tight pitch for a maximum flexibility cord
- flexible, light, good applications in high temperature and low pressure ranges

Options:

- polyester base fabric for more durability
- crush-proof or insulated versions
- anti-abrasion liners (inside or outside)
- wire free cuffs
- external scuff jackets
- stainless steel wire

UNI V2						
Diameter Inside	Diameter Outside	Weight	Bendradius	Pressure	Vacuum	Standard Length
mm	mm	g/m	mm	bar	mm WS/mm WG	m
19	21.00	80	9	1.50	5300	4
22	24.00	85	11	1.50	5300	4
25	27.00	120	12	1.40	5300	4
32	34.00	130	16	1.40	5000	4
38	40.60	165	19	1.40	5000	4
41	43.60	177	21	1.30	4500	4
44	46.60	199	22	1.20	4400	4
51	53.60	250	25	1.20	4400	4
57	63.60	280	28	1.10	4000	4
63	65.60	300	31	1.10	4000	4
70	73.14	395	35	1.10	3500	4
76	79.14	410	38	1.00	3500	4
83	86.14	470	41	1.00	3000	4
89	92.14	495	44	0.90	2950	4
95	98.14	540	47	0.90	2700	4
102	105.14	570	51	0.90	2600	4
108	111.14	680	54	0.80	2300	4
114	117.14	730	57	0.80	2100	4
121	124.14	760	60	0.80	1900	4
127	130.14	805	63	0.80	1700	4
140	143.14	885	70	0.80	1500	4
152	155.60	1050	76	0.60	1400	4
160	163.90	1090	80	0.60	1200	4
178	182.10	1210	89	0.60	1000	4
203	207.10	1380	101	0.50	700	4
229	233.60	1490	114	0.40	600	4
254	258.60	1650	127	0.40	500	4
305	309.60	2000	152	0.10	300	4

Other diameters: 26, 28, 40, 42, 45, 50, 52, 55, 58, 60, 62, 65, 67, 72, 80, 90, 91, 92, 100, 106, 110, 125, 130, 148, 150, 155, 156, 165, 180, 200, 210, 216

Other lengths spliced: 5 - 60 coils